

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 06-057730
(43)Date of publication of application : 01.03.1994

(51)Int. CI. E02D 3/00
B09B 3/00
C04B 28/02
E02D 27/34
//(C04B 28/02
C04B 18:10
C04B 22:04)


(21)Application number : 04-210334 (71)Applicant : FUJITA CORP
(22)Date of filing : 06.08.1992 (72)Inventor : NAKAMURA MASAHIRO
KANDA TORU

(54) METHOD OF LIQUEFACTION PREVENTIVE CONSTRUCTION OF GROUND BY USING
INCINERATED ASH

(57) Abstract:

PURPOSE: To use incineration ash treated as waste as the construction material for a liquefaction countermeasure ground against an earthquake.

CONSTITUTION: Air is forwarded to paste 7, in which incineration ash 1, cement 2, water 3, a water reducing agent 4 and aluminum impalpable powder 5 are kneaded in a mixer 6, and a mixture, in which a foaming agent 8 and water 3 are kneaded, by a compressor 9, and bubbles 11 discharged from a foaming nozzle 10 are kneaded by a blender 12, thus manufacturing air milk 13. Air milk 13 is force-fed to a ground area, in which a liquefaction phenomenon is generated at the time of an earthquake, by a pump, thus constructing a liquefaction countermeasure ground.



LEGAL STATUS

[Date of request for examination] 28.01.1997

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 2736720

[Date of registration] 16.01.1998

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998, 2003 Japan Patent Office